









SCHÖNBRUNN droplank click

V1.01 – 07/17

	Format / Format	1511 × 227 mm
	Anzahl Dekore / Nombre de dessins	5
	Gesamtdicke / Épaisseur totale	8.1 mm
	Nutzschicht / Couche d'usure	0.55 mm
	Stuhlrolleneignung / Chaises à roulette	Typ W / EN 425
	Brandklasse / Comportement au feu	Bfl-S1 / EN 13501-1
	Formaldehydemission / Emissions de formaldéhyde	Class E1 / EN 717-1
	Trittschall Verbesserung / Isolation phonique	16 db
	Wärmedurchlasswiderstand / Résistance thermique	0.101m ² K/W / EN 12667
	Lichtechtheit / Tenue à la lumière	> 6 ISO105 B02
	Verriegelung / Verrouillage	Välinge 5G
	Gewicht m ² / Poids m ²	7470 g
	Klassifizierung / Classification	33, 41 / EN 685
		
	Kante / Bord	Microfase 4-seitig / micro-biseau 4 côtés
	Rutschfestigkeit / Résistance au glissement	R10
	Oberfläche / Surface	UV Coating
	Synchronpore / Enregistré en relief	Ja / oui
	Material / Matériau	Phthalatfrei / sans phtalate
	Verpackungseinheit / Unité de vente	6 Stk. / pcs = 2.058 m ²
	Karton/Palette / Carton/Palette	40 = 82.320 m ²